BOBCAT COMPANY PRICE PAGES NA EXCAVATORS – E63, E85



Please note the following when using Bobcat Price Pages:

- All prices are shown in U.S. dollars.
- Check BobcatNET Pricing Homepage for current Canadian exchange rate.
- For current Dealer Installed Accessories pricing, reference BobQuote or Dealer Parts Department.
- Prices and specifications are subject to change without notice.

THE FOLLOWING UPDATES HAVE BEEN MADE TO THIS DOCUMENT:

Date	Description of Change
04/08/2013	Added E63 and E85 excavator models. Moved E60 and E80 to the discontinued model section.
01/01/2016	Effective Friday, January 1 st , 2016 Bobcat Company has adjusted the SLP of select options and power units.

^{*}Specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

E63 (Tier 4)BOBCAT HYDRAULIC EXCAVATOR



STANDARD EQUIPMENT

- Auto-Idle
- Auto-Shift, Two Speed Travel
- Auxiliary Hydraulics w/ Quick Couplers & Selectable Flow Rates
- Boom Load Hold Valve
- Boom Swing
- Cab, Enclosed with HVAC ROPS/TOPS
 - Includes: Cup Holder, Retractable Seat Belt,
 Deluxe Cloth Suspension Seat with High Back
- Control Console Locks
- Control Pattern Selector Valve (ISO/STD)
- Direct-to-tank Valve
- Dozer Blade w/ Float

- Engine Monitor with Return to Idle
- Fingertip Auxiliary Hydraulics & Boom Swing
- Horn
- Hydraulic Joystick Controls
- Mirrors Left and Right Side
- Password Protection System
- Rubber Tracks
- Tier 4 Compliant DPF/DOC
- Travel Motion Alarm
- Warranty: 12 Months, Unlimited Hours
- Work Lights
- X-ChangeTM Attachment Mounting System


Engine Model (Tier 4)	4TNV98C
Horsepower	59.4
Rated Speed-RPM	2100 RPM
Auxiliary Hydraulics Flow	22.5 GPM
Travel Speed (Maximum)	2.9 MPH
Operating Weight	13,779 lbs.
Shipping Weight	13,419 lbs.
Cab Height	100.4"
Width	78.0"
Length, Transport	18' 8"
Dig Depth	13' 6"
Maximum Reach	20' 5"
Dump Height	14'
Boom Swing (Left)	70°
Boom Swing (Right)	50°
Bucket Breakout Force	9,731 lbf.
Arm Breakout Force	5,767 lbf.

E63 (Tier 4)BOBCAT HYDRAULIC EXCAVATOR

D	CoamicmError	
PART	COMPACT EXCAVATOR	
NUMBER	DESCRIPTION	SLP IN US \$
M5563	E63 COMPACT EXCAVATOR (EQUIPPED WITH TIER 4 ENGINE)	\$82,628
PART	FACTORY INSTALLED OPTIONS	
NUMBER	DESCRIPTION	SLP IN US\$
M5563-R02-C02	STEEL TRACKS	\$1,030
PART	DEALER INSTALLED ACCESSORIES - ORDER FROM SALES	
Number	DESCRIPTION	SLP IN US\$
7120486	LASER RECEIVER, CR600	\$730
PART	DEALER INSTALLED ACCESSORIES - ORDER FROM PARTS	
Number	DESCRIPTION	
To ensure havi	ng the correct Part Number for a Dealer Installed Accessory, obtain the excavat	or model
	ber and check with the Dealer Parts Department. For the most current Dealer 1	
	Accessories pricing, refer to BobQuote or Dealer Parts Department.	
7179686	BEACON KIT Estimated Installation Time: 0.5 hr.	\$
7252156	CASE DRAIN KIT	\$
7243377	Estimated Installation Time: 1 In: ENGINE BLOCK HEATER KIT Estimated Installation Time: 1 In:	\$
6904762	EXCAVATOR OPERATOR SAFETY DVD	\$
6903186	Includes both English and Spanish versions on one DVD EXCAVATOR OPERATOR TRAINING KIT	\$
6900916	EXCAVATOR SERVICE SAFETY TRAINING KIT	\$
See Your Parts De	partment for Available Radio Options:	•
_	RADIO KIT - AM/FM WITH CD PLAYER	\$
	RADIO KIT - AM/FM WITH CASSETTE PLAYER	\$
7178255	ROOF GUARD KIT	\$
5 010700	Estimated Installation Time: 0.5 hr.	ф
7010699	SEAT BELT, 3" KIT Estimated Installation Time: 1 hr.	>
7244735	SECONDARY AUXILIARY HYDRAULICS KIT	\$
	Provides 9.2 GPM maximum flow. Estimated Installation Time: 4 hrs.	
7179688	STROBE KIT	\$
	Estimated Installation Time: 0.5 hr.	
7178233	TRANSFER PUMP KIT	\$

E85 (Tier 4)

BOBCAT COMPACT EXCAVATOR



STANDARD EQUIPMENT

- Auto-Idle
- Auto-Shift, Two Speed Travel
- Auxiliary Hydraulics w/ Quick Couplers & Selectable Flow Rates
- Boom Load Hold Valve
- Boom Swing
- Cab, Enclosed with HVAC ROPS/TOPS
 - Includes: Cup Holder, Retractable Seat Belt,
 Deluxe Cloth Suspension Seat with High Back
- Control Console Locks
- Control Pattern Selector Valve (ISO/STD)
- Direct-to-tank Valve

- Dozer Blade w/ Float
- Engine/Hydraulic Monitor with Engine Idle
- Fingertip Auxiliary Hydraulics & Boom Swing
- Horn
- Mirrors Left and Right Side
- Password Protection System
- Rubber Tracks
- Tier 4 Compliant DPF/DOC
- Travel Motion Alarm
- Warranty: 12 Months, Unlimited Hours
- Work Lights

E ' M 11/I / ' T' /)	4TN 11 100 C
Engine Model (Interim Tier 4)	4TNV98C
Horsepower	59.4
Rated Speed-RPM	2100 RPM
Auxiliary Hydraulics Flow	26.4 GPM
Travel Speed (Maximum)	2.9 MPH
Operating Weight	18,960 lbs.
Shipping Weight	18,546 lbs.
Cab Height	104"
Width	91"
Length, Transport	20' 7"
Dig Depth	15' 6"
Maximum Reach	23' 11"
Dump Height	16' 5"
Boom Swing (Left)	70°
Boom Swing (Right)	55°
Bucket Breakout Force	14,509 lbf.
Arm Breakout Force	8,069 lbf.

E85 (Tier 4)BOBCAT COMPACT EXCAVATOR

PART	COMPACT EXCAVATOR	
Number	DESCRIPTION	SLP IN US \$
M5583	E85 COMPACT EXCAVATOR (EQUIPPED WITH TIER 4 ENGINE)	\$103,927
PART	FACTORY INSTALLED OPTIONS	
Number	DESCRIPTION	SLP IN US \$
M5583-R02-C02	STEEL TRACKS	\$1,030
PART	DEALER INSTALLED ACCESSORIES – ORDER FROM SALES	
Number	DESCRIPTION	SLP IN US \$
7120486	LASER RECEIVER, CR600	\$730
PART	DEALER INSTALLED ACCESSORIES - ORDER FROM PARTS	
NUMBER	DESCRIPTION	
	ber and check with the Dealer Parts Department. For the most current Dealer Accessories pricing, refer to BobQuote or Dealer Parts Department.	<u>Installed</u>
7179686	BEACON KIT	\$
7252158	Estimated Installation Time: 0.5 hr. CASE DRAIN KIT Estimated Installation Time: 1 hr.	\$
7243377	ENGINE BLOCK HEATER KIT	\$
6904762	EXCAVATOR OPERATOR SAFETY DVD Includes both English and Spanish versions on one DVD	\$
6903186	EXCAVATOR OPERATOR TRAINING KIT	\$
6900916	EXCAVATOR SERVICE SAFETY TRAINING KIT	\$
SEE YOUR PARTS	S DEPARTMENT FOR AVAILABLE RADIO OPTIONS:	φ
	RADIO KIT - AM/FM WITH CD PLAYERRADIO KIT - AM/FM WITH CASSETTE PLAYER	\$ \$
7178255	ROOF GUARD KIT	φ \$
	Estimated Installation Time: 0.5 hr.	Ψ
7010699	SEAT BELT, 3" KIT Estimated Installation Time: 1 hr.	\$
7244736	SECONDARY AUXILIARY KIT	\$
7179688	STROBE KIT Estimated Installation Time: 0.5 hr.	\$
7178251	TRANSFER PUMP KIT Estimated Installation Time: 0.5 hr. Estimated Installation Time: 1.75 hrs.	\$

Discontinued Models

The following models have been discontinued and are no longer available: E60 & E80. Check dealer inventory for availability.

E60 (Interim Tier 4) BOBCAT HYDRAULIC EXCAVATOR



STANDARD EQUIPMENT

- Auto-Idle
- Auxiliary Hydraulics, Primary with Quick Couplers
- Auxiliary Hydraulics, Secondary with Quick Couplers
- Boom Load Holding Valve
- Boom Swing
- Control Console Locks
- Control Pattern Selector Valve (ISO/STD)
- Dozer Blade
- Engine Monitor with Return to Idle
- Enclosed Cab with Heater and Air Conditioning
 - Includes: Cup Holder, Retractable Seat Belt, Deluxe Cloth Suspension Seat with High Back

- Roll Over Protective Structure (ROPS) Meets Requirements of ISO 12117-2: 2008
- Tip Over Protective Structure (TOPS) Meets Requirements of ISO 12117: 2000
- Horn
 - Hydraulic Joystick Controls
- Mirror
- Rubber Tracks
- Spark Arrestor Muffler
- Two-Speed Travel
- Warranty: 12 Months, Unlimited Hours
- Work Lights
- X-ChangeTM Attachment Mounting System


Engine Model (Interim Tier 4)	
Horsepower	
Rated Speed-RPM	
Auxiliary Hydraulics Flow	
Primary Auxiliary 26.0 GPM	
Secondary Auxiliary 9.0 GPM	
Travel Speed (Maximum) 2.4 MPH	
Operating Weight	
Shipping Weight	
Cab Height 100.4"	
Width	
Length, Transport	
Dig Depth	
Maximum Reach	
Dump Height 13' 6"	
Boom Swing (Left) 70°	
Boom Swing (Right) 50°	
Bucket Breakout	
Dipper Breakout 5,152 lbf.	

E60 (Interim Tier 4) BOBCAT HYDRAULIC EXCAVATOR

PART	COMPACT EXCAVATOR	
Number	DESCRIPTION	SLP IN US\$
7175409	E60 COMPACT EXCAVATOR (EQUIPPED WITH 1T4 ENGINE)	\$74,455
PART	FACTORY INSTALLED OPTIONS	
Number	DESCRIPTION	SLP IN US\$
7175409-R02-C02	STEEL TRACKS	\$1,030
PART	DEALER INSTALLED ACCESSORIES – ORDER FROM SALES	
Number	DESCRIPTION	SLP IN US\$
7120486	LASER RECEIVER, CR600	\$730
PART	DEALER INSTALLED ACCESSORIES - ORDER FROM PARTS	
Number	DESCRIPTION	
	g the correct Part Number for a Dealer Installed Accessory, obtain the excavate ber and check with the Dealer Parts Department. For the most current Dealer Accessories pricing, refer to BobQuote or Dealer Parts Department.	
7179686	BEACON KIT Estimated Installation Time: 0.5 hr.	\$
6904762	EXCAVATOR OPERATOR SAFETY DVD Includes both English and Spanish versions on one DVD	\$
6903186	EXCAVATOR OPERATOR TRAINING KIT	\$
6900916	EXCAVATOR SERVICE SAFETY TRAINING KIT	\$
See Your Parts Dep	partment for Available Radio Options:	ф
	RADIO KIT - AM/FM WITH CD PLAYERRADIO KIT - AM/FM WITH CASSETTE PLAYER	\$
7179355		Φ
7178255	ROOF GUARD KIT	p
7010699	SEAT BELT, 3" KIT	\$
7176909	SPECIAL APPLICATIONS KIT (FOGS LEVEL I – FRONT & TOP GUARD) Estimated Installation Time: 2 hrs.	\$
7179688	STROBE KIT	\$
7178233	TRANSFER PUMP KIT	\$
7174370	TRAVEL MOTION ALARM KIT Estimated Installation Time: 5 hrs.	\$

E80 (Interim Tier 4)

BOBCAT COMPACT EXCAVATOR



STANDARD EQUIPMENT

- Auto-Idle
- Auxiliary Hydraulics with Quick Couplers
- Boom Load Holding Valve
- Boom Swing
- Control Console Locks
- Control Pattern Selector Valve (ISO/STD)
- Dozer Blade
- Engine Monitor with Return to Idle
- Enclosed Cab with Heater and Air Conditioning
 - Includes: Cup Holder, Retractable Seat Belt,
 Deluxe Cloth Suspension Seat with High Back

- Roll Over Protective Structure (ROPS) Meets Requirements of ISO 12117-2: 2008
- Tip Over Protective Structure (TOPS) Meets Requirements of ISO 12117: 2000
- Horn
- Hydraulic Joystick Controls
- Mirror
- Rubber Tracks
- Spark Arrestor Muffler
- Two-Speed Travel
- Warranty: 12 Months, Unlimited Hours
- Work Lights

Engine Model (Interim Tier 4)	Yanmar 4TNV98-ZWDB8
Horsepower	57
Rated Speed-RPM	2200 RPM
Auxiliary Hydraulics Flow	31.7 GPM
Travel Speed (Maximum)	2.9 MPH
Operating Weight	18,689 lbs.
Shipping Weight	18,275 lbs.
Cab Height	106.3"
Width	90.6"
Length, Transport	20' 3"
Dig Depth	15' 4"
Maximum Reach	24' 7"
Dump Height	16' 8"
Boom Swing (Left)	70°
Boom Swing (Right)	55°
Bucket Breakout	12,280 lbf.
Dipper Breakout	7,659 lbf.

E80 (Interim Tier 4) BOBCAT COMPACT EXCAVATOR

PART	COMPACT EXCAVATOR	
NUMBER	DESCRIPTION COMPACT EXCAVATOR	SLP IN US\$
7167606	E80 COMPACT EXCAVATOR (EQUIPPED WITH IT4 ENGINE)	\$94,318
PART	FACTORY INSTALLED OPTIONS	
Number	DESCRIPTION	SLP IN US\$
7167606-R02-C02	STEEL TRACKS Increases operating weight by 110 lbs.	\$1,030
PART	DEALER INSTALLED ACCESSORIES – ORDER FROM SALES	
Number	DESCRIPTION	SLP IN US\$
7120486	LASER RECEIVER, CR600	\$730
PART	DEALER INSTALLED ACCESSORIES - ORDER FROM PARTS	
NUMBER	DESCRIPTION	
	ber and check with the Dealer Parts Department. For the most current Dealer Accessories pricing, refer to BobQuote or Dealer Parts Department.	<u>Installed</u>
7179686	BEACON KIT	\$
6904762	EXCAVATOR OPERATOR SAFETY DVD	\$
6903186	EXCAVATOR OPERATOR TRAINING KIT	\$
6900916	EXCAVATOR SERVICE SAFETY TRAINING KIT	\$
See Your Parts Dep	partment for Available Radio Options: RADIO KIT - AM/FM WITH CD PLAYER	\$
	RADIO KIT - AM/FM WITH CD I LAYER	\$ \$
7178255	ROOF GUARD KIT	\$
7010699	Estimated Installation Time: 0.5 hr. SEAT BELT, 3" KIT	\$
7176910	Estimated Installation Time: 1 hr. SPECIAL APPLICATIONS KIT (FOGS LEVEL II-FRONT & TOP GUARD)	\$
	Estimated Installation Time: 2 hrs.	T
7178245	SECONDARY AUXILIARY KIT	\$
7179688	STROBE KIT	\$
7178251	TRANSFER PUMP KIT	\$
7178247	TRAVEL MOTION ALARM KIT Estimated Installation Time: 5 hrs.	\$